AUTOMATIC TRANSMISSION FLUIDS · OEM-SPECIFIC ATF

# AUTOTRANS 134 FE.

AUTOTRANS 134 FE is a premium, fully synthetic, low viscosity automatic transmission fluid developed to meet the requirements of the latest Mercedes-Benz 7G-Tronic Plus transmissions.

| 4.7 cSt | 0.840 | -49 °C | Blue |
|---|---|---|---|
| Viscosity @ 100°C | Specific Gravity @ 15.6 | Pour point | Appearance |

## APPLICATION

- Mercedes-Benz 722.9+
- 722.9FE+ 7-speed transmissions
- hybrid 724.2 transmissions

### NOT RECOMMENDED

- × **Transmissions specifying a fluid type not listed in the approvals above**
- × **Use as a hydraulic or gear oil unless the OEM explicitly permits it**

## BENEFITS

- Smooth, consistent shift quality from cold start through to full operating temperature
- Shear-stable viscosity holds the correct hydraulic pressure over the fill life
- Protects clutch plates and friction material against glazing and shudder
- Excellent low-temperature fluidity for cold-morning engagement

## PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

| | |
|---|---|
| **MB** | 236.15, A001 989 78 03 09 |
| **ATF** | 134 FE |

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Appearance<br>Visual | | **Blue** |
| Specific Gravity @ 15.6°C | | **0.840** |
| Kinematic Viscosity @ 100°C | | **4.7 cSt (typical)** |
| Pour Point<br>ASTM D97 | °C | **-49** |

Typical values, not a specification.

### PACK SIZES

25 L, 205 L, 1000 L IBC. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963