AUTOMATIC TRANSMISSION FLUIDS · DCT & CVT FLUIDS

AUTOTRANS MULTIVEHICLE CVT FLUID.

AUTOTRANS MULTIVEHICLE CVT FLUID is a premium, high performance, fully synthetic fluid designed to meet the exacting specifications of Continuously Variable Transmissions (CVT) found in many modern vehicles.

7.3 cSt	0.850	186 °C
Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point

APPLICATION

- Continuously Variable Transmissions (CVT) in vehicles from BMW/MINI
- Chrysler/Jeep
- Ford
- Fiat
- GM
- Honda
- Hyundai/Kia
- Jatco
- Mazda
- Mercedes-Benz
- Mitsubishi
- Nissan
- Peugeot
- Renault
- Subaru
- Suzuki
- Toyota/Lexus
- Vauxhall/Opel
- Volvo
- VW/Audi

NOT RECOMMENDED

- × **Transmissions specifying a fluid type not listed in the approvals above**
- × **Use as a hydraulic or gear oil unless the OEM explicitly permits it**

BENEFITS

- Smooth, consistent shift quality from cold start through to full operating temperature
- Shear-stable viscosity holds the correct hydraulic pressure over the fill life
- Protects clutch plates and friction material against glazing and shudder
- Excellent low-temperature fluidity for cold-morning engagement
- Carries 30 industry and OEM approvals, simplifying product consolidation

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963

AUTOMATIC TRANSMISSION FLUIDS · DCT & CVT FLUIDS · CONTINUED

AUTOTRANS MULTIVEHICLE CVT FLUID.

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

BMW/MINI	EZL799
	EZL799A, CVT+4, J4, NS-2/2V, NS-3, FE
MINI	COOPER ZF CVT V1
CHRYSLER/JEEP	NS-2
FORD	M2C 928-A (CFT 23), M2C 933-A (CFT 30)
FIAT	CVT N.G.
GM	DEX CVT
CVTF	I-Green2
HONDA	HMM, HCF-2
HYUNDAI/KIA	CVT-1
MAZDA	JWS 3320
MERCEDES-BENZ	MB 236.20
MITSUBISHI	CVTF-J1
NISSAN	NS-1
PEUGEOT	PSA 9735EF
RENAULT	Elf Matic CVT
SUBARU	iCVT
SUZUKI	CVTF TC
TOYOTA/LEXUS	CVTF TC
VAUXHALL/OPEL	7-sp CVT
VOLVO	CVT 4959
VW/AUDI	TL 521 16, G 052 516

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Yellow/amber**
Specific Gravity @ 15.6°C		**0.850**
Kinematic Viscosity @ 100°C		**7.3 cSt (typical)**
Flash Point (closed cup)	°C	**186**

Typical values, not a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.