AUTOMATIC TRANSMISSION FLUIDS · MULTI-VEHICLE ATF

AUTOTRANS MV.

AUTOTRANS MV is a premium, multi-vehicle, fully synthetic fluid primarily designed to meet the requirements of the latest automatic transmissions of Asian/Far Eastern origin found in many Japanese and Korean vehicles.

6.3 cSt	0.850	Red
Viscosity @ 100°C	Specific Gravity @ 15.6	Appearance

APPLICATION

- Honda
- Mazda
- Mitsubishi
- Nissan
- Toyota
- Kia and Hyundai automatic transmissions
- European OEMs using JATCO and Aisin Warner transmissions (Jaguar, Land Rover, VW/Audi)
- Applications specifying GM Dexron VI

NOT RECOMMENDED

- × **Transmissions specifying a fluid type not listed in the approvals above**
- × **Use as a hydraulic or gear oil unless the OEM explicitly permits it**

BENEFITS

- Smooth, consistent shift quality from cold start through to full operating temperature
- Shear-stable viscosity holds the correct hydraulic pressure over the fill life
- Protects clutch plates and friction material against glazing and shudder
- Excellent low-temperature fluidity for cold-morning engagement
- Carries 25 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

GM	Dexron VI
FORD	Mercon-LV, M2C 922-A1
JASO	M315 Class 1A
AISIN	WARNER AW-1F21
ATF	JWS 3309
	3324N402
JATCO	K17
BMW	83 22 0 397 114
Chrysler/Jeep	MS 9602, ATF +4
HONDA	DW-1Z1
HYUNDAI/KIA	SP-IV, SPH-IV
JAGUAR	ATF 3100 PL085
LAND	ROVER LRN402
MAZDA	FZ
MITSUBISHI	ATF-J3
NISSAN	Matic SN402
SUBARU	ATF-HP
SUZUKI	ATF 33143317
TOYOTA/LEXUS	WS, JWS 3324
VOLVO	97342 (AT102)
VW/AUDI	G 055 540

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963

AUTOMATIC TRANSMISSION FLUIDS · MULTI-VEHICLE ATF · CONTINUED

AUTOTRANS MV.

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Red**
Specific Gravity @ 15.6°C		**0.850**
Kinematic Viscosity @ 100°C		**6.3 cSt (typical)**

Typical values, not a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC. Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England
+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk
Registered in England 05866783
VAT 889171963