AUTOMATIC TRANSMISSION FLUIDS · HEAVY DUTY ATF

AUTOTRANS SYNTH HEAVY DUTY.

The commercial vehicle automatic fluid: Allison TES-295 alongside C4, plus Voith, Volvo AT101, MAN, Mercedes-Benz 236.9 and the ZF TE-ML listings that cover bus and truck automatics.

7.6 cSt	0.844	187 °C	–43 °C
Viscosity @ 100°C	Specific Gravity @ 15	Flash point	Pour point

APPLICATION

- Bus and coach automatic transmissions
- Allison TES-295 applications
- Voith retarders and transmissions
- Heavy vehicle automatics on extended drain

NOT RECOMMENDED

- × **Transmissions specifying a fluid type not listed in the approvals above**
- × **Use as a hydraulic or gear oil unless the OEM explicitly permits it**

BENEFITS

- Smooth, consistent shift quality from cold start through to full operating temperature
- Shear-stable viscosity holds the correct hydraulic pressure over the fill life
- Protects clutch plates and friction material against glazing and shudder
- Excellent low-temperature fluidity for cold-morning engagement
- Carries 9 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

GM	Dexron IIIH, IIIG, IIE
FORD	Mercon V
Allison	C4, TES-295
Voith	H55.6336 (G1363)
VOLVO	97340, 97341 (AT101)
MB	236.9
CAT	TO-2
MAN	339 Z1, V1, Z2
ZF	TE-ML 02F, 03D, 14A, 14B, 17C, 20B, 20C

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Red**
Specific Gravity @ 15°C		**0.844**
Kinematic Viscosity @ 100°C	cSt	**7.6**
Flash Point	°C	**187**
Pour Point	°C	**–43**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963