AUTOMATIC TRANSMISSION FLUIDS · OEM-SPECIFIC ATF

# AUTOTRANS TYPE G.

A Type G fluid - non friction-modified, which is the whole distinction.

| 7.4 cSt | 0.865 | >200 °C | Red |
|---|---|---|---|
| Viscosity @ 100°C | Specific Gravity @ 15 | Flash point | Appearance |

## APPLICATION

- Ford Type G specified transmissions
- John Deere J21A applications
- Older non friction-modified automatics
- Where a Dexron fluid must not be used

### NOT RECOMMENDED

- × **Transmissions specifying a fluid type not listed in the approvals above**
- × **Use as a hydraulic or gear oil unless the OEM explicitly permits it**

## BENEFITS

- Smooth, consistent shift quality from cold start through to full operating temperature
- Shear-stable viscosity holds the correct hydraulic pressure over the fill life
- Protects clutch plates and friction material against glazing and shudder
- Excellent low-temperature fluidity for cold-morning engagement

## PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

| | |
|---|---|
| **FORD** | ESP M2C-33G, ESP M2C-33F |
| **John Deere** | J21A |

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Appearance<br>Visual | | **Red** |
| Specific Gravity @ 15°C | | **0.865** |
| Kinematic Viscosity @ 100°C | cSt | **7.4 (typical)** |
| Flash Point | °C | **>200** |
| Copper Corrosion<br>ASTM D130 | | **Nil** |

Typical values, not a specification.

### PACK SIZES

1 L, 5 L, 20 L, 205 L Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963