AUTOMOTIVE · GEAR & AXLE OILS

# AXLE-PRO GEAR OILS 80W-90.

A premium API GL-5 / MT-1 hypoid axle oil carrying the full modern heavy-duty approval set, including SAE J2360 - which is the one that actually means something.

| 205.3 cSt | 15.0 cSt | 0.899 |
|---|---|---|
| Viscosity @ 40°C | Viscosity @ 100°C | Density @ 15.6 |

## APPLICATION

- The standard heavy-duty axle fill
- Commercial vehicle drive axles
- General haulage and distribution fleets

### NOT RECOMMENDED

- × **Engines specifying a viscosity grade or OEM approval not listed above**
- × **Two-stroke engines, unless a dedicated two-stroke product is specified**

## PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

| | |
|---|---|
| **API** | GL-5, MT-1 |
| **MIL-PRF** | 2105E |
| **SAE** | J-2360 |
| **SCANIA** | STO 1:0 |
| **MACK** | GO-J |
| **Arvin** | Meritor Axles |
| **MAN** | 342 Type M2 |
| **MB** | 235.20 (80w90) |
| **ZF** | TE-ML 05A, TE-ML 07A, TE-ML 12E, TE-ML 16B, TE-ML 17B, TE-ML 19B, TE-ML 21A |

## BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 16 industry and OEM approvals, simplifying product consolidation

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Density @ 15.6°C | | **0.899** |
| Viscosity @ 40°C | cSt | **205.3** |
| Viscosity @ 100°C<br>ASTM D445 | cSt | **15.0** |
| Viscosity Index<br>ASTM D2270 | | **105** |

Typical values, not a specification.

### PACK SIZES

20 L; 205 L; 1000 L IBC; Bulk

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963