COMMERCIAL VEHICLES · TRANSMISSION & AXLE OILS

AXLE-PRO S GEAR OIL 75W-140.

A heavy-duty synthetic axle and transmission oil formulated to the latest OEM gear-oil requirements, built for the demanding duty cycles of modern truck and bus drivelines.

225.4 cSt	28.2 cSt	0.873
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15.6

APPLICATION

- Modern commercial vehicle transmissions and axles
- Non-synchronised manual transmissions requiring API MT-1
- Off-highway and plant driveline applications

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 8 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	GL-4, GL-5, MT-1
MIL-PRF	2105E
SAE	J-2360
SCANIA	STO 1:0
MACK	GO-J
Arvin	Meritor Axles
ZF	TE-ML 05A, 05B, 07A, 08, 12B, 16F, 19C

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Density @ 15.6°C		**0.873**
Viscosity @ 40°C	cSt	**225.4**
Viscosity @ 100°C ASTM D445	cSt	**28.2**
Viscosity Index ASTM D2270		**162.3**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963