SPECIALITIES · AEROSOLS & SPRAYS

CHAIN & GEAR LUBE SPRAY.

Tacky aerosol chain lubricant that sprays thin to penetrate the link, then sets to a clinging film that resists fling-off at speed.

APPLICATION

- Drive and conveyor chains
- Motorcycle final drive chains
- Open gears and sprockets

NOT RECOMMENDED

- × **Any use outside the stated dilution or application instructions**
- × **Mixing with a product of a different inhibitor technology**

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system - aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

Industrial	chain grade

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Type		**Adhesive chain lubricant**
Base Oil Viscosity ASTM D445	°C	**220 cSt @ 40**
Fling Resistance		**High**
Temperature Range	°C	**-10 to +150**
Penetration		**Low viscosity on application**

Typical values, not a specification.

PACK SIZES

400 ml aerosol, 500 ml aerosol, 12 x 500 ml case

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963