INDUSTRIAL OILS · CIRCULATING & TURBINE OILS

CIRCULATING OIL 32.

A zinc-free, ashless R&O turbine and circulating oil - one of the most versatile fluids in the industrial range, and the reason it carries approvals across turbine, gear, hydraulic and compressor standards simultaneously

32 cSt	5.5 cSt	0.869	220 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15	Flash point

APPLICATION

- Steam and gas turbine lubrication systems
- Paper machine and mill circulation systems
- Air compressors requiring an ashless R&O oil
- Hydraulic systems specified to Denison HF-0

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
ISO Viscosity @ 40°C		**32**
ISO Viscosity @ 100°C		**5.5**
Density @ 15°C ASTM D4052		**0.869**
Pour Point	°C	**-26**
Flash Point °C (COC)		**220**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load
- Carries 12 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

DIN	51515 Part 1 (TD- Turbine Oils), 51517 Part 2 (CL- Gear Oils), 51524 Part 2 (HLP- Hydraulic Oils), 51506 VDL (Piston Air Compressor Oils)
British	Standard 489:1999 (R & O Turbine Oils)
Denison	HF-0
CEGB	Standard 207001
General	Electric GEK 32568 A/C
	MIL-L-17672 D
Brown	Boveri HTGD 90117
Cincinnati	Milacron P54, P57
US	Steel 120 (R & O Hydraulic Fluids)

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963