INDUSTRIAL OILS · COMPRESSOR OILS

COMPRESSOR OIL 100.

An ashless mineral compressor oil for reciprocating and rotary machines.

103 cSt	11.3 cSt	0.891
Viscosity @ 40°C	Viscosity @ 100°C	Density

APPLICATION

- Reciprocating air compressors on 2,000 hour service
- Rotary vane compressors
- Workshop and general plant air supply
- Machines where the builder specifies DIN 51506 VDL

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

DIN	51506 VDL (Piston Air Compressor Oils)

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
SAE Viscosity No.		**30**
Viscosity @ 40°C		**103**
Viscosity @ 100°C ASTM D445		**11.3**
Density		**0.891**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963