INDUSTRIAL OILS · COMPRESSOR OILS

COMPRESSOR OIL SYNTH 150.

A full synthetic PAO compressor oil for operators who want to stop changing oil every few months.

150 cSt	0.8	210 °C	-40 °C
Viscosity @ 40°C	Relative Density @ 15°C / 4	Flash point	Pour point

APPLICATION

- Rotary screw compressors on extended drain
- Continuously running plant air systems
- Unheated compressor houses
- Sites cutting compressor oil changes from 2,000 to 8,000 hours

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

DIN	51506 (VDL)
ISO	DP 6521 (DAG)

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Relative Density @ 15°C / 4°C		**0.8**
Pour Point	°C	**-40**
Flash Point, COC °C min		**210**
Viscosity, cSt @ 40°C		**150**
Rust (ASTM D 665 A)		**Pass**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963