OFF-HIGHWAY & AGRICULTURE · DRIVE TRAIN FLUIDS

DRIVE TRAIN FLUID TO-4 10W.

A Caterpillar TO-4 drive train fluid, and one of the few places in lubrication where using a better oil makes things worse.

APPLICATION

- Cold climates and winter working
- Hydraulic systems calling for a TO-4 10W
- Machines specified 10W for the transmission

NOT RECOMMENDED

- × **Hydraulic systems requiring a fire-resistant or biodegradable fluid**
- × **Engines with after-treatment where a low-SAPS engine oil is specified**

BENEFITS

- Formulated for high-contamination working environments - dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing
- Carries 8 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

Caterpillar	TO-4, TO-2
Allison	C4 (off road)
	Euclid, Dana
Termec	/ TTC
Komatsu	KES 07.868.1
Vickers	M-2950-S

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Dark amber liquid**
Density @ 15.6°C		**0.874**
Kinematic Viscosity @ 100°C	cSt	**4.78**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963