GREASES · SPECIALITY GREASES

ELECTROSHIELD.

A dielectric silicone-type gel for electrical work - a grease whose purpose is to insulate rather than to lubricate.

300 °C	None	2.5
Flash point	Dropping point	NLGI grade

APPLICATION

- Electrical connectors and terminals
- Battery terminals and bulb holders
- Spark plug boots and ignition components
- Switchgear and outdoor electrical enclosures

NOT RECOMMENDED

- × **Applications requiring an NSF H1 food-grade grease**
- × **Mixing with greases of a different thickener type without purging the bearing first**
- × **Continuous service above the stated upper temperature limit**

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable - will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**White translucent gel**
NLGI Classification		**2.5**
Flash Point ASTM D92	°C	**300**
Dropping point (IP132)		**None**
Copper Corrosion (IP112)		**Pass**
Worked penetration (IP50)		**240 to 270**
Operating temp. range	°C	**-55°C to +205**
Dielectric Strength at 25°C (ASTM D149)		**16kV/mm**
Dielectric Constant at 25°C (ASTM D150)		**2.8**
Permittivity at 25°C (ASTM D257)		**1.1015 ohms.cm**

Typical values, not a specification.

PACK SIZES

100 g, 500 g, 3 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963