SPECIALITIES · ANTIFREEZE & COOLANTS

# ENDURANCE LONG LIFE ANTIFREEZE 50:50.

The Endurance long-life OAT coolant ready mixed at 50:50.

## APPLICATION

- Workshop servicing of modern vehicles
- Fleet top-ups where mixing errors are a risk
- Service vehicles carrying one universal long-life fluid

### NOT RECOMMENDED

- × **Any use outside the stated dilution or application instructions**
- × **Mixing with a product of a different inhibitor technology**

## BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system - aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 18 industry and OEM approvals, simplifying product consolidation

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Appearance<br>Visual | | **Red/Orange Colour** |
| Conforms to British Standard | | **BS 6580:2010** |

Typical values, not a specification.

### PACK SIZES

5 L | 20 L | 205 L | 1000 L IBC. Other pack sizes and bulk deliveries up to 25,000 litres available on request.

## PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

| | |
|---|---|
| **BS** | 6580:2010 |
| **ASTM** | D4985, D3306 |
| **Chrysler** | MS 9176 |
| **Cummins** | 85T8-2, 90T8-4 |
| **FORD** | WSS-M97B44-D |
| **GM/Saab** | 6277M, 1899M |
| **John Deere** | H24 B1/C1 |
| **Mack** | 014G |
| **S** | 17004 |
| **MAN** | 248, 324 Type SNF |
| **Mercedes-Benz** | 325.3 (concentrate), 326.3 (pre-mixed) |
| **MTU** | MTL 5048 |
| **PSA** | Group B71 5110 |
| **RENAULT** | 41-01-001-D |
| **VAG** | G12/G12+, TL 774-D/F |
| **VOLVO** | PENTA VCS |
| **Suitable** | for G30, G33 and G34 specification fluids |

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963