COMMERCIAL VEHICLES · HEAVY DUTY DIESEL ENGINE OILS

FLEETLUBE 15W-40.

Engine oil designed to meet the requirements of both turbocharged and naturally aspirated diesel and petrol engines.

108.9 cSt	14.2 cSt	0.881	220 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point

APPLICATION

- Mixed older commercial fleets
- Turbocharged and naturally aspirated engines
- Plant, generators and agricultural machinery

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 7 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	CG-4/SJ
ACEA	E3
MB	228.3
Volvo	VDS
Mack	EO-M
MAN	271
Daimler Truck	DTFR 15B110

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963

COMMERCIAL VEHICLES · HEAVY DUTY DIESEL ENGINE OILS · CONTINUED

FLEETLUBE 15W-40.

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 15W-40**
Base Oil		**Mineral**
Specific Gravity @ 15.6°C		**0.881**
Kinematic Viscosity @ 40°C	cSt	**108.9**
Kinematic Viscosity @ 100°C	cSt	**14.2**
Viscosity Index ASTM D2270		**141**
Flash Point (COC)	°C	**220**
Pour Point ASTM D97	°C	**-32**
TBN ASTM D2896	mg KOH/g	**9.18**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.