COMMERCIAL VEHICLES · HEAVY DUTY DIESEL ENGINE OILS

FLEETLUBE HD 15W-40.

Engine oil designed to meet the requirements of turbocharged and naturally aspirated diesel and petrol engines.

108.0 cSt	15.5 cSt	0.882	217 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point

APPLICATION

- Older mixed fleets
- General plant and agricultural use
- Naturally aspirated diesel engines

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	CF-4/SG

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 15W-40**
Base Oil		**Mineral**
Specific Gravity @ 15.6°C		**0.882**
Kinematic Viscosity @ 40°C	cSt	**108.0**
Kinematic Viscosity @ 100°C	cSt	**15.5**
Viscosity Index ASTM D2270		**152**
Flash Point ASTM D92	°C	**217**
Pour Point ASTM D97	°C	**-30**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963