COMMERCIAL VEHICLES · HEAVY DUTY DIESEL ENGINE OILS

FLEETLUBE SAE 40.

Monograde mineral diesel engine oil in SAE 40.

APPLICATION

- Monograde diesel applications
- Warm-climate and export markets

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

Specification	on request

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 40**
Base Oil		**Mineral**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963