COMMERCIAL VEHICLES · HEAVY DUTY DIESEL ENGINE OILS

FLEETSTAR 15W-40.

Heavy duty diesel engine oil for long haul and mixed fleet operators requiring maximum protection under demanding conditions.

105.0 cSt	13.9 cSt	0.900	210 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15.5	Flash point

APPLICATION

- Long haul and mixed fleet operation
- Older commercial vehicles
- Plant and generating sets

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 15W-40**
Base Oil		**Mineral**
Kinematic Viscosity @ 40°C	cSt	**105.0**
Kinematic Viscosity @ 100°C	cSt	**13.9**
Viscosity Index ASTM D2270		**133**
Pour Point ASTM D97	°C	**-31**
Flash Point ASTM D92	°C	**210**
Specific Gravity @ 15.5°C		**0.900**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 13 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	CH-4/SL
ACEA	E7/E5/E3/A3/B4
MB	228.3
Volvo	VDS-2
Cummins	20071/72/76/77/78
MAN	3275
MTU	Type 2
Renault	RLD-2
Mack	E-OM+
Caterpillar	ECF-1
ZF	TE-ML 07C/04C
Global	DHD-1
Daimler Truck	DTFR 15C100

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963