COMMERCIAL VEHICLES · HEAVY DUTY DIESEL ENGINE OILS

FLEETSTAR PERFORMANCE PLUS 10W-30.

Semi-synthetic heavy duty diesel engine oil, especially suitable for vehicles equipped with after-treatment systems.

12.1 cSt	0.867	223 °C	-36 °C
Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point	Pour point

APPLICATION

- After-treatment equipped vehicles
- Fuel-economy sensitive fleet operation
- Mixed on/off-highway duty

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over the full drain interval
- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	CK-4/CJ-4/SN
ACEA	E11/E7/E9
Volvo	VDS-4.5
Renault	RLD-3
Mack	EOS-4.5
MB	228.31
Cummins	CES 20086/20081
MAN	M3775/M3575
Caterpillar	ECF-3
JASO	DH-2
Allison	TES 439
Ford	M2C171-F/M2C171-E
Deutz	DQC-III-10 LA
Detroit Diesel	DDC93K222/DDC93K218
Daimler Truck	DTFR 15C100

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963

COMMERCIAL VEHICLES · HEAVY DUTY DIESEL ENGINE OILS · CONTINUED

FLEETSTAR PERFORMANCE PLUS 10W-30.

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 10W-30**
Base Oil		**Semi-synthetic**
Kinematic Viscosity @ 100°C	cSt	**12.1**
Flash Point ASTM D92	°C	**223**
Pour Point ASTM D97	°C	**-36**
Specific Gravity @ 15.6°C		**0.867**
Sulphated Ash ASTM D874	% wt	**< 1.0**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963