COMMERCIAL VEHICLES · HEAVY DUTY DIESEL ENGINE OILS

FLEETSTAR PLUS LD 10W-40.

Fully synthetic low-SAPS heavy-duty diesel engine oil built for the longest drain intervals modern fleets run.

APPLICATION

- Extended drain long-haul fleets
- Marine auxiliary engines
- Stationary and standby generating sets

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 5 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

MAN	M3277
ACEA	E4/E7
MB-Approval	228.5
Volvo	VDS-3
Scania	LDF-2

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 10W-40**
Base Oil		**Fully synthetic**
Density @ 15°C ASTM D4052		**0.861 kg/l**
Flash Point ASTM D92	°C	**228**
Pour Point ASTM D97	°C	**-42**
TBN ASTM D2896	mg KOH/g	**13.5**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963