COMMERCIAL VEHICLES · HEAVY DUTY DIESEL ENGINE OILS

FLEETSTAR PREMIUM 15W-40.

One of the latest generation of heavy duty diesel engine oils, offering maximum protection under the most demanding conditions for engines that do not require a low SAPS formulation.

106.0 cSt	14.2 cSt	0.887	210 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point

APPLICATION

- Mixed fleets, long-distance trunking and stop/start delivery
- Euro 3 and Euro 4 engines without after-treatment
- Certain Euro 5 engines without particulate filters

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 15W-40**
Base Oil		**Mineral**
Kinematic Viscosity @ 40°C	cSt	**106.0**
Kinematic Viscosity @ 100°C	cSt	**14.2**
Viscosity Index ASTM D2270		**136**
Pour Point ASTM D97	°C	**-31**
Flash Point ASTM D92	°C	**210**
Specific Gravity @ 15.6°C		**0.887**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 12 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	CI-4/CH-4/SL
ACEA	E7/E5/A3/B4
MB	228.3
MAN	3275
Volvo	VDS-3
Renault	RLD-2
Mack	E-OM Plus
Cummins	20071/72/76/77/78
MTU	Type 2
Caterpillar	ECF-1a
Deutz	DQC III/II
Daimler Truck	DTFR 15B110

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963