SPECIALITIES · AEROSOLS & SPRAYS

# Flexy Shield Open Gear Lube Aerosol.

Flexy Shield is formulated to be suitable for use on all exposed gears, wire ropes and moving parts and the anti-fling additives ensure it will not be thrown off during use.

## APPLICATION

- exposed gears
- wire ropes and moving parts
- exposed heavy duty chains
- fifth wheels on trucks
- steel cables on overhead cranes
- situations with constant weather exposure

### NOT RECOMMENDED

- × **Any use outside the stated dilution or application instructions**
- × **Mixing with a product of a different inhibitor technology**

## BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system - aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use

## PACK SIZES

500ml aerosol in box of 12

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963