COMMERCIAL VEHICLES · TRANSMISSION & AXLE OILS

GEAR-PRO S 75W-85.

A low-viscosity, fully synthetic gear oil for modern driveline components, giving the fuel-economy benefit of a 75W-85 grade over conventional 80W/90W gear oils without giving up load-carrying performance.

64.4 cSt	11.7 cSt	0.862	215 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15.6	Flash point

APPLICATION

- Driveline components: transmissions, axles, transfer cases and final drives
- Limited-slip differentials
- Late-model passenger cars, vans, trucks and buses

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings
- Carries 17 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	GL-5 and GL-5 LS
SAE	J-2360
BMW	Hypoid Axle Oil G1/8222295532, Hypoid Axle Oil G2/8222413511, Hypoid Axle Oil G5/8222471487
BOT	448, BOT 799
DAIMLER	TRUCK DTFR 12B120 (previously MB 235.31)
FCA/FIAT	9.55550-DA8, 9.55550-DA9
FORD	M2C 942-A
HONDA	Hypoid Gear Oil HGO-1
LAND	ROVER LR052059, LR129319
LEXUS/TOYOTA	LSD Differential Oil LX
MOPAR	68083381AA
MERCEDES-BENZ	MB 235.15, MB 235.33, MB 235.62, MB 235.74
VW	G 052 190, G 052 518, G 055 190, G 060 190

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963

COMMERCIAL VEHICLES · TRANSMISSION & AXLE OILS · CONTINUED

GEAR-PRO S 75W-85.

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Density @ 15.6°C		**0.862**
Viscosity @ 40°C	cSt	**64.4**
Viscosity @ 100°C ASTM D445	cSt	**11.7**
Flash Point (COC)	°C	**215**
Pour Point ASTM D97	°C	**-51**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963