SPECIALITIES · ANTIFREEZE & COOLANTS

H/OAT LONG LIFE ANTIFREEZE.

A hybrid OAT concentrate formulated for heavy duty diesel service.

APPLICATION

- Heavy duty diesel engines specified for hybrid coolant
- VAG G11 / G48 systems
- Aluminium-intensive engines needing fast surface protection
- Scania LLC TB1451 applications

NOT RECOMMENDED

- × **Any use outside the stated dilution or application instructions**
- × **Mixing with a product of a different inhibitor technology**

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system - aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use
- Carries 7 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

BS	6580:2010
ASTM	D4985, D3306, D6210
AFNOR	NF R15-601
SAE	J 1034
SCANIA	LLC TB1451
VAG	G11, TL 774-C
	G48 specification fluid

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Blue/Green Colour**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L, 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963