GREASES · HEAVY PLANT GREASES

HAMMER GREASE.

A bentone-thickened, semi-synthetic, graphited grease developed specifically for hydraulic breakers.

1000 cSt	> 260 °C	2 / 3	Black
Viscosity @ 40°C	Dropping point	NLGI grade	Colour

APPLICATION

- Hydraulic breakers and hammers
- Pin and bush points on large earthmoving plant
- Demolition and quarrying equipment
- Impact-loaded joints running hot

NOT RECOMMENDED

- × **Applications requiring an NSF H1 food-grade grease**
- × **Mixing with greases of a different thickener type without purging the bearing first**
- × **Continuous service above the stated upper temperature limit**

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable - will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Smooth Adhesive Grease**
Colour ASTM D1500		**Black**
NLGI Classification		**2 / 3**
Thickener		**Bentone**
Base Oil		**Semi Synthetic**
Base Oil Viscosity @ 40°C (IP71)	cSt	**1000**
Oil Separation (IP121)	%	**2**
Worked Penetration (IP50)		**230 to 260**
Dropping Point (IP132)	°C	**> 260**
Water Washout (ASTM D1264) @ 38°C	%	**2**
Water Washout (ASTM D1264) @ 79°C	%	**5**
Four Ball Weld Load (IP239)		**500 kgs**
Graphite Content	%	**10**
Operating Temperature Range	°C	**-5°C to +150**

Typical values, not a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963