INDUSTRIAL OILS · CHAIN LUBRICANTS

HEAVY CHAIN OIL.

A tacky mineral chain oil built to stay on the chain.

150 cSt	0.891	Amber
Viscosity @ 40 °C	Density	Colour

APPLICATION

- Saw and conveyor chain in timber processing
- Estate and woodyard machinery
- General industrial drive chain
- Outdoor chain exposed to weather

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity @ 40 °C		**150**
Colour ASTM D1500		**Amber**
Density		**0.891**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963