AUTOMOTIVE · GEAR & AXLE OILS

HYPOID GEAR OIL SAE 90 LS GL-5.

A limited-slip hypoid axle oil.

159.0 cSt	16.1 cSt	0.900	222 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 150C	Flash point

APPLICATION

- Monograde limited-slip differentials
- Classic and competition axles
- Where SAE 90 LS is specified

NOT RECOMMENDED

- × **Engines specifying a viscosity grade or OEM approval not listed above**
- × **Two-stroke engines, unless a dedicated two-stroke product is specified**

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	GL-5
	MIL-L-2105D

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Density @ 150C	kg/m^3	**0.900**
Kinematic Viscosity @ 40°C	mm^2/s	**159.0**
Kinematic Viscosity @ 100°C	mm^2/s	**16.1**
Viscosity Index ASTM D2270		**102**
Flash Point – (COC)	°C	**222**
Pour Point (Method D 97)	°C	**–21**

Typical values, not a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963