GREASES · SEMI-FLUID & CENTRALISED GREASES

LITHIUM 00 EP.

A semi-fluid grease for centralised lubrication.

APPLICATION

- Centralised and progressive auto-lube systems
- Gearboxes designed for a slumping grease
- Long lubrication lines and small-bore tubing
- Cold weather auto-lube

NOT RECOMMENDED

- × **Applications requiring an NSF H1 food-grade grease**
- × **Mixing with greases of a different thickener type without purging the bearing first**
- × **Continuous service above the stated upper temperature limit**

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable - will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Colour & Appearance		**Smooth Semi-Fluid Grease**
Colour ASTM D1500		**Dark Brown**
NLGI Classification		**00**
Thickener		**Lithium Soap**
Base Oil		**Solvent Refined Mineral Oil**
Base Oil Viscosity @ 40°C (IP 71)	cSt	**180**
Worked Penetration (IP 50)		**400 to 430**
Copper Corrosion (IP 112)		**Pass**
Emcor (IP 220)		**0 : 0**
Four Ball Weld Load (IP 239) kgs		**315**
Timken OK Load (IP 326) lbs		**50**
Operating Temperature Range	°C	**-30°C to +110**

Typical values, not a specification.

PACK SIZES

12.5 kg, 50 kg, 180 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963