GREASES · LITHIUM GREASES

LITHIUM Z2.

A lithium grease loaded with 10% zinc oxide for extreme water resistance.

110 cSt	185 min °C	2
Viscosity @ 40°C	Dropping point	NLGI grade

APPLICATION

- Marine and dockside bearings
- Washdown areas and wet process plant
- Pumping equipment running in water
- Anywhere a standard grease washes out

NOT RECOMMENDED

- × **Applications requiring an NSF H1 food-grade grease**
- × **Mixing with greases of a different thickener type without purging the bearing first**
- × **Continuous service above the stated upper temperature limit**

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable - will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Off White, Smooth**
NLGI Classification		**2**
Thickener		**Lithium Soap**
Base Oil		**Solvent Refined Min. Oil**
Base Oil Viscosity @ 40°C		**110**
Dropping Point (IP132)	°C	**185 min**
Copper Corrosion (IP112)		**Pass**
Zinc Oxide Content	%	**10**
Worked Penetration (IP50)		**265 to 295**
Water Washout (ASTM D1264) @ 39°C	%	**2**
Water Washout (ASTM D1264) @ 79°C	%	**4**
EMCOR (IP220)		**0 : 0**
Operating Temperature Range	°C	**-30°C to +140**

Typical values, not a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963