GREASES · CALCIUM & CALCIUM SULPHONATE GREASES

LONG LIFE BOOM GREASE.

A calcium sulphonate complex grease - the premium water-resistant chemistry, and one of the few greases where the thickener itself carries load.

250 cSt	260 min °C	2
Viscosity @ 40°C	Dropping point	NLGI grade

APPLICATION

- Telescopic crane booms and wear pads
- Telehandlers and aerial lifting equipment
- Telescopic excavator booms
- High load sliding contacts exposed to weather

NOT RECOMMENDED

- × **Applications requiring an NSF H1 food-grade grease**
- × **Mixing with greases of a different thickener type without purging the bearing first**
- × **Continuous service above the stated upper temperature limit**

BENEFITS

- Stays in place under load, shock and vibration instead of being thrown off
- Resists water wash-out, protecting bearings in wet and wash-down areas
- Extended relubrication intervals reduce greasing labour and consumption
- Mechanically stable - will not soften and leak in service

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Colour & Appearance		**Off white, smooth grease**
NLGI Classification		**2**
Thickener		**Over-based calcium sulphonate**
Worked penetration		**265-295**
Viscosity @ 40°C	cSt	**250**
Dropping Point (ASTM D2265)		**260°C min**
4 Ball EP Load (ASTM D2596)		**620 kg**
Copper Corrosion (ASTM 4048)		**Pass**
Water washout (ASTM D1264)	%	**2**
Timken OK Load (ASTM 2509)		**60 lbs**
Operating Temp. Range	°C	**-20°C to +150**

Typical values, not a specification.

PACK SIZES

400 g cartridge, 3 kg, 12.5 kg, 50 kg, 180 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963