TEXTILE LUBRICANTS · FIBRE & YARN LUBRICANTS

# LUBREXEL 300W.

LUBREXEL 300W is an ester based carding and combing lubricant specifically designed to maximize fibre length and tear ratio.

## APPLICATION

- carding
- combing
- applied to fibre after the scoured wool dryer before carding
- spray application at wool dryer exit prior to binning
- drip application
- top making prior to oxidant/resin machine wash processes

### NOT RECOMMENDED

- × **Any application requiring food-grade or NSF H1 registration**
- × **Bearings and gearboxes requiring a fully formulated industrial lubricant**

## BENEFITS

- Scours out cleanly, leaving no residue to interfere with dyeing or finishing
- Controlled friction gives consistent yarn delivery and fewer end breaks
- Antistatic performance reduces fly and lint in the running position
- Blended in Britain for the textile trade continuously since 1872

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| Appearance<br>Visual | | **Pale yellow liquid** |
| SG @ 15 °C | | **0.95** |
| Viscosity @ 21 °C | | **150 – 250 secs.** |
| Ionic Character | | **Non-ionic** |
| pH (10% aqueous solution) | | **5 – 7** |

Typical values, not a specification.

### PACK SIZES

25 L, 205 L, 1000 L IBC

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963