COMMERCIAL VEHICLES · MARINE & TWO-STROKE OILS

MARINE TWO STROKE.

A premium outboard two-stroke oil blended from highly refined mineral oils and synthetic ashless additives, exceeding the NMMA TC-W3 specification for clean-burning, low-smoke performance.

8.50 cSt	0.877	>115 °C	Blue
Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point	Appearance

APPLICATION

- Water-cooled outboard two-stroke engines, high-output and small-cylinder alike
- Pre-mix and oil-injection systems (per equipment manufacturer mixing ratios)

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

BENEFITS

- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

NMMA	TC-W3
API	TD

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**Blue**
Kinematic Viscosity @ 100°C	cSt	**8.50**
Specific Gravity @ 15.6°C		**0.877**
Flash Point ASTM D92	°C	**>115**

Typical values, not a specification.

PACK SIZES

Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963