OFF-HIGHWAY & AGRICULTURE · AGRICULTURAL SPECIALITIES

MILKING MACHINE OIL.

An ISO 68 oil for the vacuum pump on a milking parlour.

APPLICATION

- Milking parlour vacuum pumps
- Rotary and vane vacuum pumps in dairy use
- Twice-daily duty in warm, humid conditions

NOT RECOMMENDED

- × **Hydraulic systems requiring a fire-resistant or biodegradable fluid**
- × **Engines with after-treatment where a low-SAPS engine oil is specified**

BENEFITS

- Formulated for high-contamination working environments - dust, water and soil ingress
- Reduces the number of products held on site by covering multiple applications
- Maintains hydraulic response across wide seasonal temperature swings
- Protects wet brakes and final drives against chatter and glazing

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
ISO Viscosity No		**68**
Density @ 15.6 °C		**0.884**

Typical values, not a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963