SPECIALITIES · AEROSOLS & SPRAYS

MULTI-PURPOSE SPRAY.

The workshop all-rounder in an aerosol - it lubricates, cleans, protects and displaces moisture from electrical connections, hinges, linkages and seized fittings.

APPLICATION

- Seized nuts, bolts and linkages
- Displacing moisture from electrics
- General workshop lubrication

NOT RECOMMENDED

- × **Any use outside the stated dilution or application instructions**
- × **Mixing with a product of a different inhibitor technology**

BENEFITS

- Formulated to a defined performance standard, not a lowest-cost recipe
- Protects the whole system - aluminium, copper, brass, solder and elastomers
- Consistent batch-to-batch quality from our own laboratory
- Available in pack sizes that suit workshop, fleet and bulk use

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

Industrial	and automotive use

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Type		**Light penetrating lubricant**
Propellant		**Non-flammable blend**
Flash Point ASTM D92	°C	**> 60**
Coverage		**Approx. 6 m² per can**
Residue		**Thin protective film**

Typical values, not a specification.

PACK SIZES

400 ml aerosol; 500 ml aerosol; 12 x 500 ml case. Other pack sizes and bulk deliveries up to 25,000 litres available on request.

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963