FOOD GRADE · FOOD GRADE GREASES

SILICONE GREASE NO.2.

A silica-thickened silicone grease with PTFE, working from -20 °C to +220 °C and formulated to resist the chemical cleaning solutions used in food and drink production.

APPLICATION

- Valve seats, O-rings and seals
- Plastic and rubber component lubrication
- Taps and fittings in food and drink plant
- High temperature sliding surfaces

NOT RECOMMENDED

- × **Applications requiring an H2 or 3H registered product**
- × **Direct food contact - H1 covers incidental contact only**

BENEFITS

- NSF H1 registered for use where incidental food contact may occur
- Supports HACCP compliance and audit requirements without a performance penalty
- Odourless and tasteless, protecting product quality if contact occurs
- Matches the performance of a conventional mineral equivalent
- Carries 6 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

FDA	listed (all ingredients)
NSF	H1 Guidelines
InS	H1 Guidelines
USDA	1998 H1 Guidelines
No	genetically-modified ingredients, nut oil or derivatives

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963

FOOD GRADE · FOOD GRADE GREASES · CONTINUED

SILICONE GREASE NO.2.

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Appearance Visual		**White, semi translucent grease**
NLGI Classification		**No.2**
Thickener		**Silica**
Base Oil		**High viscosity silicone oil**
Solid Lubricant		**PTFE**
Copper Corrosion (IP112)		**Pass**
Drop Point (IP132)		**None**
Water Washout ASTM (D1264) @380°C		**<2% max**
Dynamic Corrosion Resistance (EMCOR) (IP220)		**0:0**
Shell Four Ball (IP239)		**Weld Load: 180kg**
Shell Four Ball (IP239)		**Mean Hertz Load: 30kg**
Operating Temperature Range	°C	**-20°C to +220**

Typical values, not a specification.

PACK SIZES

400 g cartridge, 1 kg, 12.5 kg, 18 kg

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963