INDUSTRIAL OILS · SLIDEWAY OILS

SLIDEWAY OIL 100.

A machine tool slideway oil to DIN 51502 CGLP.

100 cSt	11.0 cSt	0.886	233 °C
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15	Flash point

APPLICATION

- Horizontal and vertical machine tool slideways
- Machines with combined slideway and hydraulic systems
- Grinders and lathes where chatter is a quality issue
- Carriages, guides and headstocks

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

DIN	51502 CGLP
Cincinnati	Lamb (formerly Milacron) – P53 (ISO 32), P47 (ISO 68), P50 (ISO 220)

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963

INDUSTRIAL OILS · SLIDEWAY OILS · CONTINUED

SLIDEWAY OIL 100.

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Kinematic Viscosity @ 40°C (mm2/s)		**100**
Kinematic Viscosity @ 100°C (mm2/s)		**11.0**
Flash Point (COC)	°C	**233**
Density @ 15°C ASTM D4052		**0.886**
Pour Point	°C	**-20**
Copper Corrosion 3hr @ 100°C (ASTM D130)		**Class 1**
Rust Test – Synthetic Sea Water (ASTM D665)		**Pass**
Four Ball EP Test, Wear Scar, 20kg, 60 min. (IP239)	mm	**0.25**
Timken OK Load (IP240)		**60lb**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963