INDUSTRIAL OILS · SPINDLE OILS

# SPINDLE OIL – ISO 10.

A very light, highly refined spindle oil for high-speed machine tool spindles.

| 10 cSt | 2.6 cSt | 0.848 | 162 °C |
|---|---|---|---|
| Viscosity @ 40°C | Viscosity @ 100°C | Density @ 15 | Flash point |

## APPLICATION

- High-speed CNC milling and grinding spindles
- Oil-mist and oil-air spindle systems
- Horizontal, vertical, bed and turret type machining centres
- Low pressure hydraulic control circuits

### NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

## BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

## TYPICAL PROPERTIES

| PROPERTY | UNIT | TYPICAL |
|---|---|---|
| ISO Viscosity @ 40°C | | **10** |
| ISO Viscosity @ 100°C | | **2.6** |
| Density @ 15°C<br>ASTM D4052 | | **0.848** |
| Pour Point | °C | **-26** |
| Flash Point (COC) | °C | **162** |

Typical values, not a specification.

### PACK SIZES

5 L, 20 L, 205 L

## HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

**Note:** Read and understand all precautions on container labels before using this product.

**SAR Lubricants** (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963