INDUSTRIAL OILS · INDUSTRIAL SPECIALITIES

STEAM CYLINDER OIL 1000.

The heaviest compounded steam cylinder oil, at ISO 1000 with a 315 °C flash point.

APPLICATION

- Large and superheated steam engines
- High temperature cylinder lubrication
- Stationary engines needing maximum film strength

NOT RECOMMENDED

- × **Systems requiring a fire-resistant (HFA/HFB/HFC/HFD) fluid**
- × **Food production areas where an NSF H1 registered lubricant is required**
- × **Applications above the stated maximum operating temperature**

BENEFITS

- Long oil life reduces the frequency and cost of change-outs
- Rapid air release and water separation keeps systems responsive and dry
- Excellent filterability protects servo valves and fine filtration
- Anti-wear chemistry protects pumps and gears under sustained high load

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Colour ASTM D1500		**Dark amber fluid**
Kinematic Viscosity @ 40°C (ISO 3104)	cSt	**900 – 1100**
Flash Point (ISO 2592)	°C	**315**
Density @ 15°C (ASTM D1298) kg/l		**0.931**

Typical values, not a specification.

PACK SIZES

5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963