AUTOMOTIVE · MOTORCYCLE OILS

SUPER TWO STROKE.

High performance, semi-synthetic two-stroke oil engineered for modern two-stroke engines in scooters, motorcycles and equipment.

6.95 cSt	0.872	140 °C	Red
Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point	Appearance

APPLICATION

- Two-stroke scooters and motorcycles
- Garden and grounds equipment
- Pre-mix and oil-injection systems

NOT RECOMMENDED

- × **Engines specifying a viscosity grade or OEM approval not listed above**
- × **Two-stroke engines, unless a dedicated two-stroke product is specified**

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

JASO	FD
API	TC
	ISO-L-EGD

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Type		**Semi-synthetic two-stroke oil**
Appearance Visual		**Red**
Kinematic Viscosity @ 100°C	cSt	**6.95**
Specific Gravity @ 15.6°C		**0.872**
Flash Point ASTM D92	°C	**140**

Typical values, not a specification.

PACK SIZES

1 L, 4 L, 20 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963