AUTOMOTIVE · MANUAL TRANSMISSION FLUIDS

SYNGEAR MTF 75W FE.

A full synthetic, premium quality manual transmission fluid formulated with the very latest additive technology to offer high levels of gear protection and to promote enhanced fuel economy.

36.3 cSt	6.4 cSt	0.845
Viscosity @ 40°C	Viscosity @ 100°C	Density @ 15.6

APPLICATION

- Modern passenger car manual transmissions requiring a low viscosity fuel efficient API GL-4 gear oil

NOT RECOMMENDED

- × **Engines specifying a viscosity grade or OEM approval not listed above**
- × **Two-stroke engines, unless a dedicated two-stroke product is specified**

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	GL-4
MTF	BOT 303350, JWS 2271
	M3, B71 2316 (HBVFE)
BMW	MTF LT-3
FIAT	9.55550-MZ2MZ6
FORD	M2C 200-E1, M2C 200-D3, M2C 200-D2 (dry DCT)
GM	1940004, 19259104, 19259105
NISSAN	LV MTF-1, 32001 1BY0APSA
PSA	Standard 9730A8
TOYOTA/LEXUS	08885-81001, 08885-81081
VOLVO	1161838, 1161839
VW	G 052 512 (dry DCT), G 052 171, G 052 178, G 052 527, G 055 512, G 052 726, G 060 726, G 052 529, G 055 529, G 009 317, G 070 726

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 31 industry and OEM approvals, simplifying product consolidation

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Density @ 15.6°C		**0.845**
Viscosity @ 100°C ASTM D445	cSt	**6.4**
Viscosity @ 40°C	cSt	**36.3**
Viscosity Index ASTM D2270		**160**

Typical values, not a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963