AUTOMOTIVE · MANUAL TRANSMISSION FLUIDS

SYNGEAR MTF 94.

A premium quality, semi-synthetic gearbox fluid designed for higher output manual transmissions, offering enhanced friction characteristics for cold-weather shifting, thermal degradation/oxidation resistance and high vis

64.5 cSt	10.3 cSt	0.874	>185 °C
Viscosity @ 40°C	Viscosity @ 100°C	Specific Gravity @ 15.6	Flash point

APPLICATION

- Manual transmissions requiring MTF 94 specification
- Rover 25, 45, MGF models
- Certain Land Rover vehicles
- Honda vehicles
- BMW/MINI vehicles

NOT RECOMMENDED

- × **Engines specifying a viscosity grade or OEM approval not listed above**
- × **Two-stroke engines, unless a dedicated two-stroke product is specified**

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 6 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

SAE	75w80
API	GL-4
Rover/Land	Rover MTF 94
Honda	MTF94, MTF2
BMW	MTF LT-2

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Kinematic Viscosity @ 100°C	cSt	**10.3**
Kinematic Viscosity @ 40°C	cSt	**64.5**
Viscosity Index ASTM D2270		**147**
Specific Gravity @ 15.6°C		**0.874**
Flash Point (COC)	°C	**>185**

Typical values, not a specification.

PACK SIZES

25 L, 205 L, 1000 L IBC (Other pack sizes and bulk deliveries up to 25,000 litres available on request)

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963