AUTOMOTIVE · GEAR & AXLE OILS

SYNGEAR PLUS 75W-90.

A full synthetic 75W-90 transmission and axle oil covering both API GL-4 and GL-5.

APPLICATION

- Extended-drain axles and gearboxes
- Fuel economy programmes on mixed fleets
- Applications specified 75W-90 synthetic
- Cold-start sensitive drivelines

NOT RECOMMENDED

- × **Engines specifying a viscosity grade or OEM approval not listed above**
- × **Two-stroke engines, unless a dedicated two-stroke product is specified**

BENEFITS

- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	GL-4 / GL-5

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Density @ 15.6 °C		**0.860**
Viscosity @ 100 °C	cSt	**14.3**

Typical values, not a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963