AUTOMOTIVE · PASSENGER CAR ENGINE OILS

SYNMAX 5W-40.

High-performance, full synthetic engine oil for use in both petrol and diesel engines, covering a wide spread of European OEM requirements.

14.9 cSt	225 °C	-40 °C
Viscosity @ 100°C	Flash point	Pour point

APPLICATION

- Mixed European car workshops
- High-output petrol and diesel
- Performance and Porsche A40 applications

NOT RECOMMENDED

- × **Engines specifying a viscosity grade or OEM approval not listed above**
- × **Two-stroke engines, unless a dedicated two-stroke product is specified**

BENEFITS

- Synthetic base stocks give a wider operating temperature window than mineral equivalent
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 12 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	SN/CF
ACEA	A3/B4
MB	229.1, 229.3, 229.5
Porsche	A40
Renault	RN 0700, RN 0710
Fiat	9.55535-Z2
PSA	B71 2296
GM	LL-A-025/LL-B-025
JASO	MA2

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963

AUTOMOTIVE · PASSENGER CAR ENGINE OILS · CONTINUED

SYNMAX 5W-40.

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 5W-40**
Base Oil		**Full synthetic**
Density @ 15°C ASTM D4052	g/cm^3	**0.854**
Kinematic Viscosity @ 100°C	cSt	**14.9**
Viscosity Index ASTM D2270		**168**
Flash Point ASTM D92	°C	**225**
Pour Point ASTM D97	°C	**-40**
TBN ASTM D2896	mg KOH/g	**11.02**

Typical values, not a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963