AUTOMOTIVE · PASSENGER CAR ENGINE OILS

SYNMAX CARINA LSPI 0W-20.

Premium full synthetic engine oil for petrol engines requiring protection from Low Speed Pre-Ignition (LSPI).

8.4 cSt	> 200 °C	-42 °C
Viscosity @ 100 °C	Flash point	Pour point

APPLICATION

- Turbocharged direct-injection petrol engines
- Vehicles specifying GM dexos1 Gen 2
- Downsized modern petrol units

NOT RECOMMENDED

- × **Engines specifying a viscosity grade or OEM approval not listed above**
- × **Two-stroke engines, unless a dedicated two-stroke product is specified**

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 8 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	SP, SN Plus
ILSAC	GF-6A, GF-5
GM	dexos1™ Gen 2
Ford	M2C 947-A, M2C 947-B1
Chrysler	MS-6395

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 0W-20**
Base Oil		**Full synthetic**
Kinematic Viscosity @ 100 °C	cSt	**8.4**
Density @ 15.6 °C	g/cm³	**0.841**
TBN ASTM D2896	mg KOH/g	**8.1**
Sulphated Ash ASTM D874	%	**≤ 0.8**
Flash Point ASTM D92	°C	**> 200**
Pour Point ASTM D97	°C	**-42**

Typical values, not a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963