AUTOMOTIVE · PASSENGER CAR ENGINE OILS

SYNMAX CYGNUS-RN 5W-30.

Premium full synthetic engine oil developed for modern Renault and Dacia vehicles, combining fuel efficiency with mid-SAPS after-treatment protection.

11.7 cSt	> 200 °C	-45 °C
Viscosity @ 100°C	Flash point	Pour point

APPLICATION

- Modern Renault and Dacia petrol and diesel engines
- Vehicles specifying Renault RN17
- Mixed French-marque workshops

NOT RECOMMENDED

- × **Engines specifying a viscosity grade or OEM approval not listed above**
- × **Two-stroke engines, unless a dedicated two-stroke product is specified**

BENEFITS

- Synthetic base stocks give a wider operating temperature window than mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over full drain interval
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across full service interval

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

ACEA	C3
Renault	RN17, RN0700 (backward compatible), RN0710 (backward compatible)
MB	226.52

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963

AUTOMOTIVE · PASSENGER CAR ENGINE OILS · CONTINUED

SYNMAX CYGNUS-RN 5W-30.

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 5W-30**
Base Oil		**Full synthetic**
Kinematic Viscosity @ 100°C	cSt	**11.7**
Density @ 15.6°C	g/cm^3	**0.850**
TBN ASTM D2896	mg KOH/g	**8.4**
Sulphated Ash ASTM D874	%	**< 0.8**
Flash Point ASTM D92	°C	**> 200**
Pour Point ASTM D97	°C	**-45**

Typical values, not a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963