AUTOMOTIVE · PASSENGER CAR ENGINE OILS

SYNMAX ECO-RN FE 0W-20.

Premium full synthetic, fuel-efficient engine oil formulated for modern Renault and Dacia engines requiring RN17 FE.

8.5 cSt	> 200 °C	-42 °C
Viscosity @ 100 °C	Flash point	Pour point

APPLICATION

- Renault and Dacia engines specifying RN17 FE
- Fuel-economy service schedules

NOT RECOMMENDED

- × **Engines specifying a viscosity grade or OEM approval not listed above**
- × **Two-stroke engines, unless a dedicated two-stroke product is specified**

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over the full drain interval
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

ACEA	C5
Renault	RN17 FE

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963

AUTOMOTIVE · PASSENGER CAR ENGINE OILS · CONTINUED

SYNMAX ECO-RN FE 0W-20.

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 0W-20**
Base Oil		**Full synthetic**
Kinematic Viscosity @ 100°C	cSt	**8.5**
Density @ 15.6°C	g/cm^3	**0.845**
TBN ASTM D2896	mg KOH/g	**8.2**
Viscosity Index ASTM D2270		**189**
Sulphated Ash ASTM D874	%	**< 0.8**
Flash Point ASTM D92	°C	**> 200**
Pour Point ASTM D97	°C	**-42**

Typical values, not a specification.

PACK SIZES

1 L | 5 L | 20 L | 205 L (Other pack sizes and bulk deliveries up to 25,000 litres are available on request.)

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963