AUTOMOTIVE · PASSENGER CAR ENGINE OILS

SYNMAX ECO-V 0W-20.

Full synthetic, fuel-efficient engine oil for modern turbocharged direct injection petrol engines, with LSPI protection.

8.2 cSt	> 200 °C	-48 °C	Green
Viscosity @ 100 °C	Flash point	Pour point	Colour

APPLICATION

- VW Group engines specifying 508.00/509.00
- Porsche C20 applications
- Turbocharged GDI petrol engines

NOT RECOMMENDED

- × **Engines specifying a viscosity grade or OEM approval not listed above**
- × **Two-stroke engines, unless a dedicated two-stroke product is specified**

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Protects against wear during cold starts, when most engine wear occurs
- Keeps pistons and ring packs clean, maintaining compression and fuel economy
- Compatible with catalytic converters and diesel particulate filters
- Resists oxidation and thickening across the full service interval
- Carries 6 industry and OEM approvals, simplifying product consolidation

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

ACEA	C5
API	SN Plus
VW	508.00, 509.00
Porsche	C20
Ford	M2C-956-A1

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 0W-20**
Base Oil		**Full synthetic**
Colour ASTM D1500		**Green**
Kinematic Viscosity @ 100 °C	cSt	**8.2**
Density @ 15.6 °C	g/cm³	**0.847**
TBN ASTM D2896	mg KOH/g	**8.3**
Flash Point ASTM D92	°C	**> 200**
Pour Point ASTM D97	°C	**-48**

Typical values, not a specification.

PACK SIZES

1 L, 5 L, 20 L, 205 L

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963