COMMERCIAL VEHICLES · HEAVY DUTY DIESEL ENGINE OILS

SYNMAX OMEGA XFE 5W-30.

Full synthetic, fuel efficient, low SAPS heavy duty diesel engine oil formulated for modern Euro 6 engines with emission control technology.

APPLICATION

- Latest-generation Euro 6 heavy duty diesel
- Mercedes-Benz FE models to MB 228.61
- Fleets running low-sulphur diesel under severe duty

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 5W-30**
Base Oil		**Full synthetic**
Density @ 15°C ASTM D4052	g/cm^3	**0.858**
Kinematic Viscosity @ 100°C	cSt	**12.2**
Viscosity Index ASTM D2270		**165**
NOACK	% wt	**11**
Phosphorus	% wt	**> 0.12**
Sulphated Ash ASTM D874	% wt	**< 1.0**
TBN ASTM D2896	mg KOH/g	**12.8**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over the full drain interval
- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

API	FA-4
Volvo	VDS-5
Renault	RLD-5
Mack	EOS-5
Daimler Truck	DTFR 15C130 (MB 228.61)
Cummins	CES 20087
JASO	DH-2
Detroit Diesel	93K223

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963