COMMERCIAL VEHICLES · HEAVY DUTY DIESEL ENGINE OILS

SYNMAX ORION FE 5W-30.

Full synthetic, fuel efficient, low SAPS heavy duty diesel engine oil for modern powerplants with DPF or SCR after-treatment.

APPLICATION

- Euro 6 engines with advanced emissions treatment
- Mixed fleets on extended drain
- Operation on low-sulphur diesel (50 ppm or below)

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over the full drain interval
- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

ACEA	E4/E6/E7/E8/E9/E11
API	CK-4
Volvo	VDS-4.5
Renault	RLD-3
Mack	EO-S 4.5
Scania	LDF-4
MB	228.51/228.52
MAN	M3271-1/M3575/M3677/M3775/M3777
Caterpillar	ECF-3
Cummins	CES 20086/20081
Deutz	DQC IV-18 LAM
TU	Type 2.1/3.1
JASO	DH-2
DAF	Euro 6
IVECO	18-1804

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 5W-30**
Base Oil		**Full synthetic**
Density @ 15°C ASTM D4052	g/cm³	**0.848**
Kinematic Viscosity @ 100°C	cSt	**11.9**
Viscosity Index ASTM D2270		**168**
Sulphated Ash ASTM D874	% wt	**< 1.0**
TBN ASTM D2896	mg KOH/g	**12.8**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road,
Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England
05866783
VAT 889171963