COMMERCIAL VEHICLES · HEAVY DUTY DIESEL ENGINE OILS

SYNMAX PERFORMANCE PLUS E6 10W-40.

High performance, full synthetic, low SAPS heavy duty diesel engine oil for Euro 4 to Euro 6 engines with emission control systems.

98.38 cSt	14.79 cSt	180 °C	-42 °C
Viscosity @ 40°C	Viscosity @ 100°C	Flash point	Pour point

APPLICATION

- Euro 4 to Euro 6 with DPF and SCR
- Low-SAPS fleet consolidation
- Municipal and refuse vehicles

NOT RECOMMENDED

- × **Engines requiring a full-SAPS oil where a low-SAPS product would starve the additive system**
- × **Applications calling for an API CJ-4 or older specification without checking backward compatibility**

BENEFITS

- Synthetic base stocks give a wider operating temperature window than a mineral equivalent
- Low-SAPS chemistry protects DPF, SCR and catalyst systems over the full drain interval
- Extends drain intervals, cutting downtime and cost per mile across the fleet
- Protects after-treatment systems - EGR, SCR and DPF - from ash blocking
- Controls soot-related thickening and bore polish in high-load duty cycles
- Improves fuel economy through reduced friction in the valve train and bearings

PERFORMANCE PROFILE

Suitable for use where the following specifications are required:

ACEA	E6, E7
API	CI-4
MB	228.51
Volvo	VDS-3
Mack	EO-N
Renault	RLD-2
MAN	3477
MTU	3.1
Deutz	DQC IV-10 LAD
	AFD
Daimler Truck	DTFR 15B120

SAR Lubricants (Squire A. Radcliffe & Sons Ltd)
Gill Bridge Oil Works, Lowlands Road, Mirfield, WF14 8LU, England

+44 (0)1924 494371
enquiries@sarlubricants.co.uk
sarlubricants.co.uk

Registered in England 05866783
VAT 889171963

COMMERCIAL VEHICLES · HEAVY DUTY DIESEL ENGINE OILS · CONTINUED

SYNMAX PERFORMANCE PLUS E6 10W-40.

TYPICAL PROPERTIES

PROPERTY	UNIT	TYPICAL
Viscosity Grade SAE J300		**SAE 10W-40**
Base Oil		**Full synthetic**
Density @ 15°C ASTM D4052	g/cm^3	**0.855**
Kinematic Viscosity @ 40°C	cSt	**98.38**
Kinematic Viscosity @ 100°C	cSt	**14.79**
Viscosity Index ASTM D2270		**157**
Flash Point ASTM D92	°C	**180**
Pour Point ASTM D97	°C	**-42**
Sulphated Ash ASTM D874	%	**< 1.0**
TBN ASTM D2896	mg KOH/g	**9.0**

Typical values, not a specification.

PACK SIZES

20 L, 205 L, 1000 L IBC, Bulk | Other pack sizes and bulk deliveries up to 25,000 litres are available on request.

HEALTH & SAFETY

Refer to SDS for proper handling and disposal. Please note that the SDS includes handling, health and disposal information which should be passed on to your employees, and to anyone else who comes in contact with our product. Additional advice can also be obtained from your local representative.

Note: Read and understand all precautions on container labels before using this product.